

## Smart Home control unit GFVS-TouchIV



GFVS-TouchIV, black glossy



GFVS-TouchIV, pure white glossy

### The Smart Home control unit GFVS-TouchIV – Switch on, configure and use!

15.6" monitor PC GVS-Touch II for continuous duty with integrated wireless antenna module and ready installed Wireless Visualisation and Control Software GFVS 4.0 for all the necessary sensors and actuators, 5 clients, 5 cameras and any number of sensors, actuators and timers. Smartphone link over WLAN. With stand for standalone installation or for mounting on the wall.

The **VESA mount** for wall mounting can be ordered separately.

This monitor PC has a Linux operating system and is locked for other applications so GFVS 4.0 can work free of faults. Suitable for 24/7 non-stop operation.

The scope of supply includes a mains adapter.

All data and events are saved to a database for a predefined period. There is a net memory capacity of up to 80 GB available for data. As protection against data loss, data is saved on a hard disc partition. In addition, data can be stored externally, e.g. on an USB stick.

The installed Wireless Building Visualisation and Control Software GFVS 4.0 visualises the switch positions of actuators and the consumption of taught-in meters for electricity, gas, water and heat. On the other hand, direct hook-ups and controls can be made using preset software links. One touch is all that's needed.

**Provided an internet access exists, it permits external access by smartphone and/or tablet PC for visualisation and control. This is free of charge on the building side. Very simple and secure registration using Eltako quickcon® technology.**

### Technical data

CPU	Intel® Celeron 3865U
chip set	SoC – no chipset is required
RAM	4 GB DDR 4
hard disk	120GB SSD
graphic card	Intel® HD Graphics 610
connections	2xUSB 3.0, 4xUSB 2.0, 1xRJ-45 10/100/1000 LAN, 1xHDMI, 1xVGA, Audio I/O; Wireless LAN 802.11n
antennas	1x wireless antenna EnOcean 868 MHz, 1x WLAN antenna 2,4 GHz
power consumption	7 watts (without turned-on monitor), 12 watts (with turned-on monitor)
ventilation	silent, passive Heatpipe cooling
dimensions (HxWxT)	391 x 327 x 42 mm
Mounting	100mm VESA
weight	ca. 3.6 kg

<b>GFVS-TouchIV-wg</b>	Smart Home control unit Touch PC with GFVS 4.0, pure white glossy	EAN 4010312318829	<b>999,00 €/pc.*</b>
<b>GFVS-TouchIV-sz</b>	Smart Home control unit Touch PC with GFVS 4.0, black glossy	EAN 4010312318812	<b>999,00 €/pc.*</b>
<b>VESA mounts</b>	For mounting GFVS-TouchIV on the wall	EAN 4010312312629	<b>31,00 €/pc.*</b>