



FTR55HB-wg Wireless temperature controller

Wireless temperature controller with hand wheel pure white glossy for single mounting 80x80x27 mm or mounting in the 55 mm switch system. With battery (lifetime 4 years). Smart Home sensor.

The temperature controller can be taught-in into the relay actuator TF61R or the heating cooling actuator FHK and into the GFVS software.

At a setpoint change from min. 0,15°C, the temperature controller sends a wireless telegram within 60 seconds. If there is no change, a status message is sent every 5 minutes.

A jumper defines the function mode. In the mode FHK the measured and set temperature are sent.

Measurement accuracy is approx. 1°C.

The **day reference temperature** that ranges from +12°C to +28°C is changed using the hand wheel.

In the position ❄ the temperature control is off and the frost protection function activated.

A day/night slide switch, like at the FTR65HS, is not present.

We recommend stainless-steel countersunk screws 2.9x25mm, DIN 7982 C, for screw connections. Both with rawl plugs 5x25mm and with 55mm switch boxes. Set of 2 stainless-steel countersunk screws 2,9x25mm and plugs 5x25mm are enclosed.

FTR55HB-wg	Wireless temperature controller 55x55mm with hand wheel and battery, pure white glossy	EAN 4010312317921	80,10 €/pc.
-------------------	--	-------------------	--------------------