
Staircase Time Switch TLZ12-8 The Simple



TLZ12-8







1 NO contact not potential free 16A/250V AC. Incandescent lamps up to 2000 W, energy saving lamps ESL and LED lamps up to 100 W, without switch-off early warning. Standby loss 0.7 watt only.

Modular device for DIN EN 60715 TH35 rail mounting. 1 module = 18 mm wide, 58 mm deep. **The noiseless electronics** do not even bother the sensitive ear — unlike many synchronous motors with mechanical gears.

230V control voltage, supply voltage and switching voltage.

Variable time range from approx. 0.2 to 12 minutes.

Glow lamp current up to 50 mA, dependent on the ignition voltage of the glow lamps.

Own permanent light switch with the big rotary switch.


3-wire and 4-wire circuits, resettable, with attic lighting if 4-wire circuit.

Automatic detection of the method of connection.


Without switch-off early warning function and without zero passage switching.

With double connections for pushbutton and lamp in order to connect either above or below or only below.

Typical connections




3-wire circuit, resettable



4-wire circuit with attic lighting, resettable

Function rotary switches



(5) = Permanent light switched on AUTO = The set function is active

Technical data page 15-10. Housing for operating instructions GBA12, see accessoirs, chapter Z.

TLZ12-8 EAN 4010312401637 31,40 €/pc. 1 NO 16A

