## Blisterpack dimming BPD55





## BPD55 Blisterpack dimming

## Blisterpack dimming with wireless pushbutton FT55 and universal dimmer switch FUD61NPN-230 V. Smart Home sensor and Smart Home actuator.

**FT55:** 4-way wireless pushbutton pure white glossy for single mounting 84x84x15mm or mounting into the 55 switching system. Generates the power for wireless telegrams itself when the button is pressed, therefore there is no connecting wire and no standby loss.

Wireless pushbuttons with one rocker can transmit two evaluable signals: press rocker up and press rocker down.

The mounting base can be screwed onto a flat surface or glued to the wall, on glass or on furniture using the enclosed adhesive foil. Use the sleeves in the 55 mm socket box for screw mounting.

**FUD61NPN-230V:** Universal dimmer switch, 300W power MOSFET. Automatic lamp detection. Only 0.7 watt standby loss. With adjustable minimum brightness or dimming speed. With switching operation for light alarm clocks, children's rooms and snooze function. Additionally with light scene control. Encrypted wireless, bidirectional wireless and repeater function are switchable.

For installation. 45 mm long, 45 mm wide, 33 mm deep.

Universal dimmer switch for lamps up to 300 W, dependent on ventilation conditions. Dimmable energy saving lamps ESL and dimmable 230 V-LED lamps, additionally dependent on the lamps electronics.

Zero passage switching with soft ON and soft OFF to protect lamps.

Supply voltage, switching voltage and control voltage local 230 V. No minimum load. The brightness level is stored on switch-off (memory).

the brightness level is stored on switch-on (memory).

**BPD55** Blisterpack dimming EAN 4010312317839 **138,50 €/pc.**