

FRP70-230V



FA250

1 and 2 level wireless repeater with small antenna and with antenna FA250. Only 0.6 watt standby loss. A wireless antenna FA250 is connectable as required.

Mounting in the 230V power supply cord, e.g. in false ceilings.
100mm long, 50mm wide and 25mm deep.

This repeater is only needed if the building conditions prevent undisturbed reception or the distance between the wireless pushbutton and receiver is too great. Antenna FA250 with 250cm cable is connectable instead of the enclosed antenna. The range can be extended considerably by placing it in the optimum position. The 1-level mode is activated ex works. Only wireless signals from sensors are received, tested and retransmitted at full transmit power. Wireless signals from other repeaters are ignored to reduce the data volume.

Use the rotary switch to switch over to 2 level mode. Then the wireless signals from sensors and from another 1 level repeater are processed. A signal may therefore be received and amplified twice.

The LED indicates incoming wireless signals by flashing briefly.

Wireless repeaters need not be taught-in. They receive and amplify signals from all wireless sensors within their reception area.

FRP70-230V	Wireless repeater	EAN 4010312306482	94,20 €/pc.
FA250	Wireless antenna with 250cm cable, black	EAN 4010312300244	21,10 €/pc.
FA250-gw	Wireless antenna with 250cm cable, grey white	EAN 4010312317051	21,10 €/pc.